

Flying Roses



capsules
by AGF

FREE PATTERN


XXXXXXXXXXXXXXXXXXXXXXXXXXXX

LETTERS

FABRICS DESIGNED BY AGF STUDIO




CAP-L-3000
ROSES & LETTERS



CAP-L-3001
LOVE PUZZLE



CAP-L-3002
XOXOXO



CAP-L-3003
LOVE LIFE



CAP-L-3004
GIVE LOVE



CAP-L-3005
LOVE SPECKLES



CAP-L-3006
LOVE BLOOMS



CAP-L-3007
LOVE DREAM



CAP-L-3008
LOVE MEANING



CAP-L-3009
ALL YOU NEED IS LOVE



Flying Roses

FINISHED SIZE | 20" x 60"

FABRIC REQUIREMENTS

Fabric **A** CAP-L-3000 ½ yd.
 Fabric **B** CAP-L3006 ⅙ yd.
 Fabric **C** P.E- 433 ½ yd.
 Fabric **D** DEN-S-2004 1¾ yd.

BACKING FABRIC

Fabric **D** included. (*Suggested*)

BINDING FABRIC

(Fabric **D**) (*included*)

CUTTING DIRECTIONS

¼" seam allowances are included.
 WOF means width of fabric.

- Two (2) 13⅞" x 13⅞" squares from fabric **A**
- Two (2) 13⅞" x 13⅞" squares from fabric **C**
- Two (2) 20½" x 3½" strips from fabric **B**
- One (1) 12½" x 6½" rectangle from fabric **C**
- Two (2) 15½" x 4½" strips from fabric **D**
- Two (2) 39½" x 4½" strips from fabric **D**

CONSTRUCTION

Sew all rights sides together with ¼" seam allowance.

- To start take the (1) 13⅞" x 13⅞" of Fabric **A** and place in on top of the 13⅞" x 13⅞" of Fabric C.
- Repeat.



DIAGRAM 1

XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

- Now in order to make sixteen (16) HST, use the Magic 8 method. (less time consuming)
- First draw diagonal line across both corners
- Then stitch at a ¼" away from the line on top and bottom. Use Diagram as a reference.



DIAGRAM 2

- Next place a ruler in the center of your perfect square and cut directly down center.
- Cut center horizontally.
- Then cut on both initial drawn lines.




DIAGRAM 3

- There should be a total of sixteen (16) HST



DIAGRAM 4

- Begin to piece accordingly, resembling bed runner. Use cover as reference.



DIAGRAM 5

- Keep in mind the 12½' x 6½' rectangles of Fabric C is attached on the lower section of the bed runner.
- Next sew the 4½' x 15½' of Fabric D to the 39½' x 4½' of Fabric D.
- Repeat.
- Now sew these pieces to the sides of the bed runner.
- Lastly take the two (2) 20½' x 3½' of Fabric B and sew on top and bottom on bed runner.




DIAGRAM 6

QUILT ASSEMBLY

Sew rights sides together.


- Place BACKING FABRIC on a large surface wrong side up. Stretch it with masking tape against that surface.
- Place BATTING on top of backing fabric.
- Place TOP on top of the batting with right side facing up. Smooth away wrinkles using your hands.
- Pin all layers together and baste with basting thread, using long stitches. You can also use safety pins to join the layers.
- Machine or hand quilt starting at the center and working towards the corners. Remember that quilting motifs are a matter of personal preference. Have fun choosing yours!
- After you finished, trim excess of any fabric or batting, squaring the quilt to proceed to bind it.

BINDING

Sew rights sides together.

- Cut enough strips 1½' wide by the width of the fabric D to make a final strip 170' long. Start sewing the binding strip in the middle of one of the sides of the quilt, placing the strip right side down and leaving an approximated 5' tail. Sew with ¼' seam allowance (using straight stitch), aligning the strip's raw edge with the quilt top's raw edge.
- Stop stitching ¼' before the edge of the quilt (DIAGRAM B 1). Clip the threads. Remove the quilt from under the machine presser foot. Fold the strip in a motion of 45° and upward, pressing with your fingers (DIAGRAM B2). Hold this fold with your finger, bring the strip down in line with the next edge, making a horizontal fold that aligns with the top edge of the quilt (DIAGRAM B3). Start sewing at ¼' of the border, stitching all the layers. Do the same in the four corners of the quilt.

- Stop stitching before you reach the last 5 or 6 inches. Cut the threads and remove the quilt from under the machine presser foot. Lay the loose ends of the binding flat along the quilt edge, folding the ends back on themselves where they meet. Press them together to form a crease. Using this crease as the stitching line, sew the two open ends of the binding with right sides together (you can help yourself marking with a pencil if the crease is difficult to see).
- Trim seam to $\frac{1}{4}$ " and press open. Complete the sewing. Turn binding to back of the quilt, turn raw edge inside and stitch by hand using blind stitch.



artgalleryfabrics.com

NOTE: While all possible care has been taken to ensure the accuracy of this pattern, We are not responsible for printing errors or the way in which individual work varies. Please read instructions carefully before starting the construction of this quilt. If desired, wash and iron your fabrics before starting to cut.

© 2017 Courtesy of Art Gallery Quilts LLC. All Rights Reserved.