









## FABRIC REQUIREMENTS

Fabric <b>A</b>	PE-488	¼ yd.
Fabric <b>B</b>	PE-505	¼ yd.
Fabric <b>C</b>	PE-489	¼ yd.
Fabric <b>D</b>	CAP-TK-1500	¼ yd.
Fabric <b>E</b>	CAP-TK-1501	¼ yd.

### BINDING FABRIC

Fabric **E** (Included)

## Fabric **E**

- One (1) 1" x 25" strip.
- One (1) mask template 1
- One (1) mask template 2

## CONSTRUCTION

*Sew all rights sides together with ¼" seam allowance.*

- Start by sewing all the strips in the order shown on diagram 1.



DIAGRAM 1

## CUTTING DIRECTIONS

*¼" seam allowances are included.  
WOF means width of fabric.*

### Fabric **A**

- One (1) 1¼" x 25" strip.
- Three (3) 1" x 25" strips.

### Fabric **B**

- One (1) 1¼" x 25" strip.
- Two (2) 1" x 25" strips.

### Fabric **C**

- Three (3) 1¼" x 25" strips.

### Fabric **D**

- One (1) 1½" x 25" strip.

- Rotate the template about 45° angle, and place it on the strip block. See diagram below for reference.



DIAGRAM 2





