




Snuggle



capsules
a << ▲

by AGF

FREE PATTERN





Snuggle

QUILT DESIGNED BY *AGFstudio*

pine
LULLABY
rediscovered



FABRICS DESIGNED BY *AGFstudio*



Fabric A
CAP-PL-1300
FURRIES COOL



Fabric B
CAP-PL-1312
FOREST TRAILS



Fabric C
CAP-PL-1310
MOUNTAIN PINES




Fabric D
CAP-PL-1311
STAR GLOW



Fabric E
PE-421
HONEY



Fabric F
PE-426
APRICOT CREPE




Fabric G
PE-420
CRYSTAL PINK




Fabric H
PE-425
MAUVELOS



Fabric I
PE-442
OCEAN WAVES



Fabric J
PE-408
WHITE LINEN



Fabric K
CAP-PL-1313
BEAR HUG PANEL



Fabric L (Binding)
BIN25108
WOODLANDS BOUND





DIAGRAM 12

QUILT ASSEMBLY

Sew rights sides together.

- Place BACKING FABRIC on a large surface wrong side up. Stretch it with masking tape against that surface.
- Place BATTING on top of backing fabric.
- Place TOP on top of the batting with right side facing up. Smooth away wrinkles using your hands.
- Pin all layers together and baste with basting thread, using long stitches. You can also use safety pins to join the layers.
- Machine or hand quilt starting at the center and working towards the corners. Remember that quilting motifs are a matter of personal preference. Have fun choosing yours!
- After you finished, trim excess of any fabric or batting, squaring the quilt to proceed to bind it.

BINDING

Sew rights sides together.

- Cut enough strips 2½" wide by the width of the fabric L to make a final strip 170" long. Start sewing the binding strip in the middle of one of the sides of the quilt, placing the strip right side down and leaving an approximated 5" tail. Sew with ¼" seam allowance (using straight stitch), aligning the strip's raw edge with the quilt top's raw edge.
- Stop stitching ¼" before the edge of the quilt (DIAGRAM B 1). Clip the threads. Remove the quilt from under the machine presser foot. Fold the strip in a motion of 45° and upward, pressing with your fingers (DIAGRAM B 2). Hold this fold with your finger, bring the strip down in line with the next edge, making a horizontal fold that aligns with the top edge of the quilt (DIAGRAM B 3). Start sewing at ¼" of the border, stitching all the layers. Do the same in the four corners of the quilt.
- Stop stitching before you reach the last 5 or 6 inches. Cut the threads and remove the quilt from under the machine presser foot. Lay the loose ends of the binding flat along the quilt edge, folding the ends back on themselves where they meet. Press them together to form a crease. Using this crease as the stitching line, sew the two open ends of the binding with right sides together (you can help yourself marking with a pencil if the crease is difficult to see).
- Trim seam to ¼" and press open. Complete the sewing. Turn binding to back of the quilt, turn raw edge inside and stitch by hand using blind stitch.
- If you are using our 2.5 edition (binding fabric), click or scan this QR code to see a tutorial on how to use this specialty fabric.

DIAGRAM B1



Stop stitching here

DIAGRAM B2



45°

DIAGRAM B3



fold



