Floral Envelopes

FEATURING PARADISE COLLECTION




DESIGNED WITH LOVE BY Pat Gravo

Floral Envelopes

FINISHED SIZE: 78" × 78" BLOCK SIZE: 16" × 16"

To download the instructions for this pattern visit

www.artgalleryfabrics.com







PA-208 Daylight Pond




Morning Showers



Taupe Double Bloom



Fresh Tiny Buds



Dark Chic Paper



Pink Eternal Sashes



Orchid Sparkles



Flashy Tealight



Pink Squared Fashion





Twilight Pond



Evening Showers



PA-306 Ivory Double Bloom





Light Chic Paper

PA-304		

Green Eternal Sashes



Teal Sparkles



Ashy Tealight



Blue Squared Fashion

COLOR OPTION KIT QUANTITY PA-300 2 7/8 yd. | PA-307 PA-301 1 yd. PA-308 1 yd. PA-302 2 1/2 yd. PA-306 1 yd. PA-305 1 yd. PA-304 3/4 yd. 1 yd. Backing PA-303 4 7/8 yd.

© 2010 Courtesy of Art Gallery Quilts LLC. All Rights Reserved. 3804 N 29th Ave. Hollywood, FL 33020 PH: 888.420.5399 FX: 425.799.6103





Floral Envelopes

FINISHED SIZE: 78 1/2" × 78 1/2"



FABRIC REQUIREMENTS

Fabric A PA-200 2 % yd. Fabric B PA-201 1 yd. Fabric C PA-202 2 ½ yd. Fabric D PA-205 1 yd. Fabric E PA-203 1 yd. Fabric F PA-207 2 yd. Fabric G PA-208 1 yd. Fabric H PA-206 1 yd. Fabric I PA-204 ¾ yd.

Backing PA-200 (Fabric A) 4 ½ yd. (suggested)

Binding (included)PA-200 (Fabric **A**)

CUTTING DIRECTIONS

FOR ALL BLOCKS CUT

Thirty-two (32) 17 %" x 5 %" rectangles from fabric A One (1) 4 %" square from fabric A (Cut it once diagonally) Twelve (12) 17 %" x 5 %" rectangles from fabric B Thirty-three (33) 17 %" x 5 %" rectangles from fabric C Twelve (12) 17 %" x 5 %" rectangles from fabric D Twenty-four (24) 17 %" x 5 %" rectangles from fabric F Twelve (12) 17 %" x 5 %" rectangles from fabric G Ten (10) 17 %" x 5 %" rectangles from fabric H

FOR BORDERS CUT

For Inner Border

Two (2) 681/2" by 21/2" strips from fabric I*

Two (2) 72½" by 2½" strips from fabric I*

For Outer Border

Two (2) 72½" by 3½" strips from fabric **E***

Two (2) 781/2" by 31/2" strips from fabric E*

* (in order to get these long strips you need to join two Width Of Fabric strips together)

IMPORTANT HINT FOR FABRIC PLACEMENT:


All the letters shown in color green represent the pieces or patches but ALSO represent the fabric styles explained in "FABRIC REQUIREMENTS" (notice they are also represented in the same color).

ROW CONSTRUCTION


(sew fabrics right sides together)

This quilt is constructed in diagonal rows instead of blocks. All rows are constructed the same way


- Place one fabric rectangle on your cutting mat. Make a mark on the center of one long side edge with a water soluble pen. Draw a diagonal line connecting that mark with one bottom corner. Draw another line but this time on the opposite side. Rotary cut on both lines, revealing a triangle. (DIAGRAM 1)
- Repeat the same step with all the rectangles.




- Grab two triangles. Position one triangle on top of another triangle (right sides facing together) as shown on DIAGRAM 2.
- Start sewing at the exact intersection of the two fabrics with a 1/4" seam allowance. Press seams open. (You will notice that the tip of the top triangle shows over the edge of the bottom triangle. These are called "dog ears". It is normal when you sew triangles and you will trim them out later).




 Continue adding another triangle and then another (as shown in DIAGRAM 3, in the same way you did in last step. Make sure you follow color fabric sequence in the front cover picture quilt layout, for fabric placement.



• For the first row, piece together three triangles (as shown in DIAGRAM 4. Remember to press open all seams.



• Make, in the same way row after row, until you finish all the triangles cut. DIAGRAM 5




- Trim all "dog ears". You can make this with scissors or with a rotary cutter.
- Sew the rows together (Follow the front cover picture for row placement). Take much care to match seam intersections between each row (lock them with pins if necessary). Continue joining all the rows. Press all seams toward the same direction.
- Press the WHOLE TOP with a hot steam iron.


 $^{\circ}$ Sew two fabric $\stackrel{\hbox{\scriptsize A}}{\mbox{\scriptsize small}}$ small triangles on the two corners of the top. DIAGRAM 6



• To square the top, place it on top of a large cutting mat. Using a long ruler and following one of the small corner triangles as a guide, trim excess fabric. Make sure you leave a 1/4" extra over the tip of fabric F triangles as you trim. DIAGRAM 7



 Trim in the same way the remaining three sides of the top.



BORDERS ASSEMBLY

(sew right sides together)

For the inner border

- Sew two 68 ½" by 2½" fabric I strips along the opposite sides (left & right) of the top with a ¼" seam allowance. Press open.
- Sew the other two 72 ½" by 2 ½" fabric I strips along the top and bottom sides of the top with a ¼" seam allowance. Press open.

For the outer border

- Sew two 72 ½" by 3 ½" fabric E strips along the opposite sides (left & right) of the top with a ¼" seam allowance. Press open.
- Sew the other two 78 $\frac{1}{2}$ " by 3 $\frac{1}{2}$ " fabric **E** strips along the top and bottom sides of the top with a $\frac{1}{4}$ " seam allowance. Press open.

QUILT ASSEMBLY


(sew right sides together)

- Place BACKING FABRIC on a large flat surface wrong side up. Stretch it with masking tape against that surface.
- Place BATTING on top of backing fabric.
- Place TOP on top of the batting with right side facing up. Smooth away wrinkles using your hands.
- Pin all layers together and baste with basting thread, using long stitches. You can also use safety pins to join the layers.
- Machine or hand quilt starting at the center and moving towards the EDGES in all directions.

⊕ BINDING

(sew right sides together)

- Cut enough strips 1½" wide by the width of the fabric (in length) A to make a final strip 324" long (approximately 8 strips). Start sewing the binding strip in the middle of one of the sides of the quilt, placing the strip right side down facing the quilt and leaving an approximated 5" tail loose. Sew with ½" seam allowance (using straight stitch), aligning the strip's raw edge with the quilt top's raw edge.
- Stop stitching ¼" before the end of the quilt (DIAGRAM B1). Clip the threads. Remove the quilt from under the machine presser foot. Fold the strip in a motion of 45° and upward, pressing with your fingers (DIAGRAM B2). Hold this fold with your finger, bring the strip down in line with the next edge, making a horizontal fold that aligns with the top edge of the quilt (DIAGRAM B3). Start sewing at ¼" of the border, stitching all the layers. Do the same in the four corners of the quilt.
- Stop stitching before you reach the last 5 or 6 inches. Cut the threads and remove the quilt from under the machine presser foot. Lay the loose ends of the binding flat along the quilt edge, folding the ends back on themselves where they meet. Press them together to form a crease. Using this crease as the stitching line, sew the two open ends of the binding with right sides together (you can help yourself marking with a pencil if the crease is difficult to see).
- Trim seam to ¼" and press open. Complete the sewing. Turn binding to back of the quilt, turn raw edge inside and stitch by hand using blind stitch.



CONGRATULATIONS!

NOTES: While all possible care has been taken to ensure the accuracy of this pattern, we are not responsible for printing errors or the way in which individual work varies.

Please read instructions carefully before starting the construction of this quilt. If desired, wash and iron your fabrics before starting to cut.