
NO/ADIC TAPESTRY







QUILT DESIGNED BY APRIL RHODES



FABRICS DESIGNED BY APRIL RHODES





WAN-13300



WAN-13301



WAN-13302 TEMPLE OF ASIAQ



WAN-13303





WAN-13305 GUST OF LEAVES SILVER



WAN-13306 DREAMCATHCING CELESTE



WAN-13307 SACRED SEEDS MOJAVE



WAN-13308 DIAMOND CLOTH CEREUS



WAN-13309 WANDERING LANDS BOREAS





WAN-23300



WAN-23301



WAN-23302



WAN-23303





WAN-23305 GUST OF LEAVES GOLD



WAN-23306 DREAMCATHCING FLARE



WAN-23308 DIAMOND CLOTH NOPAL



WAN-23309



WAN-23310 WANDERING LANDS MINERAL SYLPHS FREEDOM FLOWER



NO/ADIC TAPESTRY

FINISHED SIZE | 42'×51'

FABRIC REQUIREMENTS

Fabric A	WAN-13301	1/4 yd.
Fabric B	WAN-13303	1/4 yd.
Fabric C	WAN-13306	1/4 yd.
Fabric D	WAN-13308	1/4 yd.
Fabric E	WAN-13309	1/4 yd.
Fabric F	WAN-23302	1/4 yd.
Fabric G	WAN-23300	½ yd.
Fabric H	WAN-23309	1/4 yd.
Fabric I	WAN-23304	1/4 yd.
Fabric J	WAN-23310	2½ yd.
Fabric K	PE-408	34 yd.
Fabric L	PE-443	1/4 yd.
Fabric M	PE-429	1/4 yd.

BACKING FABRIC

WAN-23310- Fabric J - (included)

BINDING FABRIC

WAN-23305- 1/3 yd.

CUTTING DIRECTIONS

1/4" seam allowances are included.

- Ten (10) 2 1/2' x 6 1/2' rectangles from Fabric **A**
- Two (2) 2" x 42 1/2" strips from Fabric **B**
- Twelve (12) 4 1/4' squares from Fabric C
- Sixteen (16) 4 1/4' x 4 1/4' squares from Fabric D
- Seven (7) 4 1/4' x 4 1/4' squares from Fabric E
- Three (3) 2 1/2' x 6 1/2' rectangles from Fabric F
- Four (4) 2' x 42 1/2' strips from Fabric G
- Seven (7) 4 1/4' x 4 1/4' squares from Fabric H
- Eight (8) 4 1/4' x 4 1/4' squares Fabric I
- Eight (8) 4 1/4' from Fabric J (do not use the border motif)




- Thirty Six (36) 4 1/4' x 4 1/4' squares from Fabric K
- Eight (8) 2 1/2' x 6 1/2' rectangles from Fabric K
- Six (6) 4 1/4' x 4 1/4' squares from Fabric L
- Twelve (12) 4 1/4' squares from Fabric M
- Two (2) 42 1/2" lengths from border (bottom 7") from Fabric J
- Important Cut all squares in half diagonally.

ASSEMBLING THE TOP

Sew all rights sides together with ¼"seam allowance. Press open. Trim all half square triangles to 3 1/2" x 3 1/2".

- Make seven half square triangles with Fabric H and Fabric K.
- Now make seven half square triangles with Fabric E and Fabric K.
- Arrange half square triangle following Diagram 1 and sew together.








DIAGRAM 1

• Sew one 2' x 42 1/2' strip from Fabric G to the piece you made in Diagram 1. Tips of triangles formed with Fabric H and E will point away from this strip.


DIAGRAM 2




DIAGRAM 2



- Now make six half square triangles with Fabric L and Fabric K.
- \bullet Arrange half square triangle following Diagram 3 and sew together. DIAGRAM 3








DIAGRAM 3

• Sew piece you made in Diagram 3 to the piece you created in Diagram 2, with tips of green triangles pointing away from 2' x 42 1/2' strip from Fabric G.

DIAGRAM 4




DIAGRAM 4

 \bullet Sew piece you created in Diagram 4 to one 2' x 42 1/2' strip from Fabric B. $\,$ DIAGRAM 5




DIAGRAM 5

 Repeat steps in Diagram 1-5. You will need a total of two pieces that look like Diagram 6. Set these pieces aside.






DIAGRAM 6

• Using 12 triangles from Fabric C and 12 triangles from Fabric M, assemble 3 blocks as shown. DIAGRAM 7




DIAGRAM 7

 Using 16 triangles from Fabric D, 8 triangles from Fabric J and 8 triangles Farbic K,assemble 4 blocks as shown. DIAGRAM 8




DIAGRAM 8

• Piece all 7 blocks together, as shown. DIAGRAM 9



DIAGRAM 9

 Repeat steps in Diagram 7-9. You will need a total of two pieces that look like Diagram 9. • Using two 2 1/2' x 6 1/2' rectangles from Fabric K and one 2 1/2' x 6 1/2' rectangle from Fabric A. Sew together as shown. Repeat three more times.




DIAGRAM 10

 Using two 2 1/2' x 6 1/2' rectangles from Fabric A and one 2 1/2' x 6 1/2' rectangle from Fabric F attach as shown. Repeat two more times. DIAGRAM 11




DIAGRAM 11

• Assemble these 7 blocks as shown. DIAGRAM 12



DIAGRAM 12

• Attach one 2' x 42 1/2' strip from Fabric G to the bottom and top of the piece you created in Diagram 12.




DIAGRAM 13

• Attach all the pieces you have sewn together following Diagram 14. .




DIAGRAM 14

 Finally attach Fabric J borders to top and bottom with motif pointing out away from the body of the quilt top: like tassels on the edge of a tapestry! Follow quilt illustration as a guide.

QUILT ASSEMBLY

Sew rights sides together.


- Use the left over fabric from Fabric J for your quilt back. Place BACKING FABRIC on a large surface wrong side up. Stretch it with masking tape against that surface.
- Place BATTING on top of backing fabric.
- Place TOP on top of the batting with right side facing up. Smooth away wrinkles using your hands.
- Pin all layers together and baste with basting thread, using long stitches. You can also use safety pins to join the layers.
- Machine or hand quilt starting at the center and working towards the corners. Remember that quilting motifs are a matter of personal preference. Have fun choosing yours!
- After you finished, trim excess of any fabric or batting, squaring the quilt to proceed to bind it.



BINDING

Sew rights sides together.

- Cut enough strips 1½' wide by the width of the WAN-23305 to make a final strip 203' long. Start sewing the binding strip in the middle of one of the sides of the quilt, placing the strip right side down and leaving an approximated 5' tail. Sew with ¼' seam allowance (using straight stitch), aligning the strip's raw edge with the quilt top's raw edge.
- Stop stitching ½' before the edge of the quilt (DI-AGRAM B 1). Clip the threads. Remove the quilt from under the machine presser foot. Fold the strip in a motion of 45° and upward, pressing with your fingers (DIAGRAM B2). Hold this fold with your finger, bring the strip down in line with the next edge, making a horizontal fold that aligns with the top edge of the quilt (DIAGRAM B3). Start sewing at ½' of the border, stitching all the layers. Do the same in the four corners of the quilt.
- Stop stitching before you reach the last 5 or 6 inches. Cut the threads and remove the quilt from under the machine presser foot. Lay the loose ends of the binding flat along the quilt edge, folding the ends back on themselves where they meet. Press them together to form a crease. Using this crease as the stitching line, sew the two open ends of the binding with right sides together (you can help yourself marking with a pencil if the crease is difficult to see).
- Trim seam to ¼' and press open. Complete the sewing. Turn binding to back of the quilt, turn raw edge inside and stitch by hand using blind stitch.



Congratulations & enjoy



artgalleryfabrics.com

NOTE: While all possible care has been taken to ensure the accuracy of this pattern. We are not responsible for printing errors or the way in which individual work varies.

Please read instructions carefully before starting the construction of this quilt. If desired, wash and iron your fabrics before starting to cut.

© 2015 Courtesy of Art Gallery Quilts LLC. All Rights Reserved.