Worlds Apart








Worlds Apart

BLOCKS DESIGNED BY AGE STUDIOAGE Studio



PRINTEMPS FUSION

FABRICS DESIGNED BY AGF STUDIO



FUS-P-1200 PAINTED DESERT PRINTEMPS



FUS-P-1201 SCATTER PRINTEMPS




FUS-P-1202 LUMINOUS FIELD PRINTEMPS



FUS-P-1203 FRESHLY PICKED PRINTEMPS



FUS-P-1204



FUS-P-1205 PLAID BEAT PRINTEMPS



FUS-P-1206



FUS-P-1207 PERENNIAL PRINTEMPS



FUS-P-1208 ROUNDED SEEDS PRINTEMPS



FUS-P-1209 MAGNOLIA PRINTEMPS







FINISHED SIZE | 80 × 80

FABRIC REQUIREMENTS

Fabric A PE-408 1/3 yd.
Fabric B FUS-P-1201 3/4 yd.
Fabric C PE-420 3/4 yd.
Fabric D FUS-P-1203 1 1/4 'yd.
Fabric E FUS-P-1206 1 1/4 'yd
Fabric F PE-472 1 3/8' yd.
Fabric G PE-464 11/6' yd.
Fabric H FUS-P-1209 1/2' yd.

BINDING FABRIC
PE-472 (Fabric F)

BACKING FABRIC

FUS_P-1206 (Fabric E) 4yds

CUTTING DIRECTIONS

1/4" seam allowances are included. WOF means width of fabric.

Cut two (2) 4 1/2" x WOF strips from fabric A

- Cut six (6) 4 1/2" x WOF strips from fabric B
- Cut six (6) 4 1/2" x WOF strips from fabric C
- Cut eight (8) 4 1/2" x WOF strips from fabric D
- Cut ten (10) 4 1/2" x WOF strips from fabric E
- \bullet Cut eight (8) 4 1/2" x WOF strips from fabric F
- $\bullet\,$ Cut six (6) 4 1/2" x WOF strips from fabric ${\bf G}$
- $\bullet\,$ Cut four (4) 4 1/2" x WOF strips from fabric H

CONSTRUCTION

Sew all rights sides together with $\frac{1}{4}$ seam allowance.

- You will create five different combinations with the strips of fabric you previously cut.
- Every combination will be repeated two (2) times
- Follow the diagram below for fabric combinations, placement and attachment.
- Combination a join fabric (A, B, C, D, E) strips TWO TIMES






DIAGRAM 1

- Cut every 4 1/2" sixteen (16) times
- Combination **b** join fabric (**B, C, D, E, F**) strips TWO TIMES




• Combination c join fabric (C, D, E, F, G) strips TWO




• Cut every 4 1/2" sixteen (16) times

 Combination d join fabric (C, D, E, F, G) strips TWO TIMES



- Cut every 4 ½" sixteen (16) times
- Combination e join fabric (E, F, G, H, B) strips TWO TIMES



- Cut every 4 1/2" sixteen (16) times
- Block assembly

DIAGRAM 5

- Attach the 4½' strips you just cut in the following order to create your quilt blocks. Repeat the same block eight (8) times and then create another eight (8) mirrored units.
- Refer to the diagram below to create your blocks.




DIAGRAM 6

• Attach your blocks in the following order:




DIAGRAM 7

QUILT ASSEMBLY


Sew rights sides together.

- Place BACKING FABRIC on a large surface wrong side up. Stretch it with masking tape against that surface.
- Place BATTING on top of backing fabric.
- Place TOP on top of the batting with right side facing up. Smooth away wrinkles using your hands.
- Pin all layers together and baste with basting thread, using long stitches. You can also use safety pins to join the layers.
- Machine or hand quilt starting at the center and working towards the corners. Remember that quilting motifs are a matter of personal preference. Have fun choosing yours!
- After you finished, trim excess of any fabric or batting, squaring the quilt to proceed to bind it.

BINDING

Sew rights sides together.

- Cut enough strips 1½' wide by the width of the fabric **F** to make a final strip 330' in long. Start sewing the binding strip in the middle of one of the sides of the quilt, placing the strip right side down and leaving an approximated 5' tail. Sew with ¼' seam allowance (using straight stitch), aligning the strip's raw edge with the quilt top's raw edge.
- Stop stitching ¼' before the edge of the quilt (DIA-GRAM B 1). Clip the threads. Remove the quilt from under the machine presser foot. Fold the strip in a motion of 45° and upward, pressing with your fingers (DIAGRAM B2). Hold this fold with your finger, bring the strip down in line with the next edge, making a horizontal fold that aligns with the top edge of the quilt (DIAGRAM B3). Start sewing at ¼' of the border, stitching all the layers. Do the same in the four corners of the quilt..



- Stop stitching before you reach the last 5 or 6 inches. Cut the threads and remove the quilt from under the machine presser foot. Lay the loose ends of the binding flat along the quilt edge, folding the ends back on themselves where they meet. Press them together to form a crease. Using this crease as the stitching line, sew the two open ends of the binding with right sides together (you can help yourself marking with a pencil if the crease is difficult to see).
- Trim seam to ¼' and press open. Complete the sewing. Turn binding to back of the quilt, turn raw edge inside and stitch by hand using blind stitch.
- Congrats! You've finished your Worlds Apart uilt!





artgalleryfabrics.com

NOTE: While all possible care has been taken to ensure the accuracy of this pattern, We are not responsible for printing errors or the way in which individual work varies

Please read instructions carefully before starting the construction of this quilt. If desired, wash and iron your fabrics before starting to cut.