

Twinkle

FINISHED SIZE | 19' x 24'

FABRIC REQUIREMENTS

| | | |
|----------|---------|-------|
| Fabric A | KC-1113 | ¾ yd. |
| Fabric B | KC-1110 | ¾ yd. |
| Fabric C | KS-116 | ½ yd. |

BACKING FABRIC

Fabric B - ¾ yd (Included)

BINDING FABRIC

Fabric C - ½ yd

CUTTING DIRECTIONS

¼" seam allowances are included.
WOF means width of fabric.

- One (1) 19½" x 24½" rectangle of **I NEED SOME SPACE** from Fabric A
- One (1) 19½" x 24½" rectangle from Fabric B

CONSTRUCTION

Sew all rights sides together with ¼" seam allowance.

- Take your Fabric A piece and quilt if desired placing Batting Fabric on the wrong side of your Fabric A piece.
- Pin all layers together and baste with basting thread, using long stitches. You can also use safety pins to join the layers.
- Place Backing fabric on top of your Fabric A piece, wrong side facing
- Machine or hand quilt starting at the center and working towards the corners. Remember that quilting motifs are a matter of personal preference. Have fun choosing yours!
- After you finished, trim excess of any fabric or batting, squaring the quilt to proceed to bind it.

BINDING

Sew rights sides together.

- Cut enough strips 1½" wide by the width of the fabric C to make a final strip 96" long. Start sewing the binding strip in the middle of one of the sides of the quilt, placing the strip right side down and leaving an approximated 5" tail. Sew with ¼" seam allowance (using straight stitch), aligning the strip's raw edge with the quilt top's raw edge.
- Stop stitching ¼" before the edge of the quilt (**DIAGRAM B 1**). Clip the threads. Remove the quilt from under the machine presser foot. Fold the strip in a motion of 45° and upward, pressing with your fingers (**DIAGRAM B 2**). Hold this fold with your finger, bring the strip down in line with the next edge, making a horizontal fold that aligns with the top edge of the quilt (**DIAGRAM B 3**). Start sewing at ¼" of the border, stitching all the layers. Do the same in the four corners of the blanket.
- Stop stitching before you reach the last 5 or 6 inches. Cut the threads and remove the blanket from under the machine presser foot. Lay the loose ends of the binding flat along the quilt edge, folding the ends back on themselves where they meet. Press them together to form a crease. Using this crease as the stitching line, sew the two open ends of the binding with right sides together (you can help yourself marking with a pencil if the crease is difficult to see).
- Trim seam to ¼" and press open. Complete the sewing. Turn binding to back of the quilt, turn raw edge inside and stitch by hand using blind stitch.

DIAGRAM B1




DIAGRAM B2



DIAGRAM B3

