



DESIGNED BY AGEstudio



FABRICS DESIGNED BY AGF STUDIO





SNS-13013 YOU ARE MAGIC



SNS-13005 SWEET TOOTH

# ADDITIONAL BLENDERS FOR THIS PROJECT



 $\begin{array}{c} \text{PE-436} \\ \text{CREME DE LA CREME} \end{array}$ 



PE-481 MAGNETISM



PE-480 STEEL



PE-449 MANDARIN



PE-406 BURNT ORANGE



PE-425 MAUVELOUS





# FABRIC REQUIREMENTS

Fabric A	SNS-13013	1 yd.
Fabric B	PE-436	⅓syd.
Fabric C	PE-481	¾yd.
Fabric D	PE-480	¹⁄₄ yd.
Fabric <b>E</b>	PE-449	¹⁄₄yd.
Fabric <b>F</b>	PE-406	½ yd.
Fabric <b>G</b>	PE-425	⅓ yd.
Fabric <b>H</b>	SNS-1305	<sup>3</sup> ⁄ <sub>4</sub> yd.

## CUTTING DIRECTIONS

1/4" seam allowances are included. WOF means width of fabric.

#### Fabric A:

Six (6) 14" x 18" rectangles. (See diagram 1)

#### Fabric **B**:

One (1) 26" x 3" strip.

#### Fabric C:

- One (1) 26" x 3" strip.
- (2) Template 1.
- (1) Template 2.

#### Fabric D:

Two (2) 26" x 3" strips.

#### Fabric E:

• Two (2) 26" x 3" strips.

#### Fabric F:

• One (1) 26" x 3" strip.

#### Fabric G:


• One (1) 26" x 3" strip.

#### Fabric H:

Two (2) 14" x 18" rectangles.

## CONSTRUCTION

 Take fabric A and cut it into (6) 14" x 18" panels, which we will call panel 1, 2, 3, 4, 5, and 6. See diagram below for reference.



Panel 1

Panel 4



Panel 2



Panel 5





DIAGRAM 1

- For the construction of this project we will be applying the French seam technique.
- Take panel 5 and 6 from fabric **A**, using ½" seam allowance sew the sides and bottom of both panels facing wrong sides together.
- Press, and trim about  $\frac{1}{8}$ " from the edge (See Figure 3 for reference)
- Turn the sewn panels inside out, press, and using a ½" seam allowance sew again.









 ${\rm DIAGRAM}~2$ 

- Fold the top edge around  $\frac{1}{4}$ ", press and fold it again at  $\frac{3}{4}$ ".
- Press and edge stitch from the second fold.





DIAGRAM 3

• Take (1) 26" x 3" strips from fabric **G**, and gate

• Single half fold, press, and top stitch.

fold ¾", press.

- Fold the small edges to ½" and edge stitch. from the raw edge
- Repeat the same step with (1) 26" x 3" strips from fabric D to make the other strap.




DIAGRAM 4

- Take one of the straps and measure about 4" from the sides, and lined up to the ¾" fold at the top of the tote.
- Pin the strap aligning the edge to the seam of the top of the tote and sew. Repeat the same step on the other sides.





DIAGRAM 5

To make the other bags from the panel use the following combinations:

- Pair panel 1 with 2, and use fabric C and D for straps.
- Pair panel 3 with 4, and use fabric B and D for straps.



DIAGRAM 6

### Appliqué bag.

- Take (2) template 1 and (1) template 2 from fabric
  C, place them on (1) 14" x 18" rectangle from fabric
- With a zig zag stitch or a stitch of your choice sew around each template.
- Please see diagram below for template placement.



DIAGRAM 7

- Follow the same steps on how to make the tote, but instead of using the panels, use (2) 14" x 18" rectangles from fabric H.
- For straps use (1) 26" x 3" from fabric **E** and **F**.
- See templates at the end of the instructions.
  Enjoy.

# Congratulations & enjoy




artgalleryfabrics.com

NOTE: While all possible care has been taken to ensure the accuracy of this pattern, We are not responsible for printing errors or the way in which individual work varies.

Please read instructions carefully before starting the construction of this quilt. If desired, wash and iron your fabrics before starting to cut.

 $\ \odot$  2020 Courtesy of Art Gallery Quilts LLC. All Rights Reserved.



**1"** Test square