Dulcet







QUILT DESIGNED BY AGEstudio





FABRICS DESIGNED BY AGF STUDIO



CAP-SV-11601 WINDBLOOMS



CAP-SV-11600 MOMENT OF ZEN



CAP-SV-11602 PETAL TRELLIS

ADDITIONAL BLENDERS FOR THIS PROJECT



PE-432 SANDSTONE



DSE-715 CAFE LATTE



FE-504 SAND



DEN-L-4000 SOFT SAND



FINISHED SIZE | 60" × 60"

FABRIC REQUIREMENTS

Fabric A CAP-SV-11601 1 1/8 yd. Fabric B PE-432 1 1/8 yd. Fabric C DSE-715 1 3/8 yd. Fabric D CAP-SV-11600 1 1/8 yd. Fabric E FE-504 1 1/8 yd. Fabric F DEN-L-4000 1 1/8 yd.

BACKING FABRIC

CAP-SV-11602- 4 yds. (Suggested)

BINDING FABRIC

DSE-715 (Fabric C) (Included)

CUTTING DIRECTIONS

1/4" seam allowances are included.

- One hundred and forty four (144) $5\frac{1}{2}$ " x 3" rectangles from fabric A.
- One hundred and forty four (144) 3" squares from fabric B.
- One hundred and forty four (144) 3" squares from fabric C.
- One hundred and forty four (144) $5\frac{1}{2}$ " x 3" rectangles from fabric **D**.
- One hundred and forty four (144) 3" squares from fabric **E**.
- One hundred and forty four (144) 3" squares from fabric F.

CONSTRUCTION

Sew all rights sides together with ¼"seam allowance.

Flying Geese Construction:

- Bring thirty six (36) 5½" x 3" rectangles from fabric A, thirty six (36) 3" squares from fabrics B and C.
- Place one (1) 3" square from fabric B on top of the fabric A rectangle.
- Align it to the left side of the rectangle, right sides facing together and draw a diagonal line on top of the square following the diagram below.



DIAGRAM 1

- Stitch on the drawn line.
- Trim excess fabric leaving 1/4" seam allwance and press open.



DIAGRAM 2

- Take one (1) 3" square from fabric C and align it on the right side of the fabric A rectangle, right sides facing together.
- Draw a diagonal line on top of the square.
- Stitch on the drawn line.
- Trim excess fabric leaving 1/4" seam allowance and press open.
- Repeat these steps to have a total of thirty six (36) BAC flying geeses.




DIAGRAM 3

- Repeat the same flying geese instructions by taking thirty six (36) 5½" x 3" rectangles from fabric A and thirty six (36) 3" squares from fabrics B and F.
- Create a total of thirty six (36) BAF.



DIAGRAM 4

- Repeat the same flying geese instruction by taking seventy two (72) 5½" x 3" rectangles from fabric A and seventy two (72) 3" squares from fabrics C and F.
- Create a total of seventy two (72) CAF.



DIAGRAM 5

- Repeat the same flying geese instruction by taking thirty six (36) 5½" x 3" rectangles from fabric D and thirty six (36) 3" squares from fabric E and F.
- Create a total of thirty six (36) EDF.



DIAGRAM 6

- Repeat the same flying geese instruction by taking thirty six (36) 5½" x 3" rectangles from fabric D and thirty six (36) 3" squares from fabric B and E.
- Create a total of thirty six (36) BDE.



DIAGRAM 7

- Repeat the same flying geese instruction by taking thirty six (36) 5½" x 3" rectangles from fabric D and thirty six (36) 3" squares from fabric B and E.
- Create a total of thirty six (36) EDB.



DIAGRAM 8

- Repeat the same flying geese instruction by taking thirty six (36) 5½" x 3" rectangles from fabric D and thirty six (36) 3" squares from fabric C and E.
- Create a total of thirty six (36) EDC.



DIAGRAM 9

• Join one (1) BAC with one (1) EDF.



DIAGRAM 10

• Join one (1) BAF with one (1) EDC.



DIAGRAM 11

• Join one (1) CAF with one (1) BDE.



DIAGRAM 12

• Join one (1) CAF with one (1) EDB.




DIAGRAM 13

- Now join each block following the diagram below.
- Repeat the same construction creating a total of thirty six (36) blocks.
- Each block should measure 10½" x 10½".




DIAGRAM 14

• Now, take two (2) block and join them.





DIAGRAM 15

• Take two (2) more blocks and join them.



DIAGRAM 16

• Take one piece and rotate it 180° and join it at the bottom part of the other assembled piece, following the diagram below.



 ${\rm DIAGRAM}~17$

- Create a total of nine (9) blocks.
- Each block should measure 20½".




DIAGRAM 18

• To assemble your quilt top, join each block by columns.




DIAGRAM 19




DIAGRAM 20

QUILT ASSEMBLY


 $Sew\ rights\ sides\ together.$

- Place BACKING FABRIC on a large surface wrong side up. Stretch it with masking tape against that surface.
- Place BATTING on top of backing fabric.
- Place TOP on top of the batting with right side facing up. Smooth away wrinkles using your hands.
- Pin all layers together and baste with basting thread, using long stitches. You can also use safety pins to join the layers.
- Machine or hand quilt starting at the center and working towards the corners. Remember that quilting motifs are a matter of personal preference. Have fun choosing yours!
- After you finished, trim excess of any fabric or batting, squaring the quilt to proceed to bind it.

BINDING

Sew rights sides together.

- Cut enough strips 1½" wide by the width of the fabric C to make a final strip 250" long. Start sewing the binding strip in the middle of one of the sides of the quilt, placing the strip right side down and leaving an approximated 5" tail. Sew with ¼" seam allowance (using straight stitch), aligning the strip's raw edge with the quilt top's raw edge.
- Stop stitching ½" before the edge of the quilt (DIAGRAM B 1). Clip the threads. Remove the quilt from under the machine presser foot. Fold the strip in a motion of 45° and upward, pressing with your fingers (DIAGRAM B2). Hold this fold with your finger, bring the strip down in line with the next edge, making a horizontal fold that aligns with the top edge of the quilt (DIAGRAM B3). Start sewing at ¼" of the border, stitching all the layers. Do the same in the four corners of the quilt.
- Stop stitching before you reach the last 5 or 6 inches. Cut the threads and remove the quilt from under the machine presser foot. Lay the loose ends of the binding flat along the quilt edge, folding the ends back on themselves where they meet. Press them together to form a crease. Using this crease as the stitching line, sew the two open ends of the binding with right sides together (you can help yourself marking with a pencil if the crease is difficult to see).
- Trim seam to ¼" and press open. Complete the sewing. Turn binding to back of the quilt, turn raw edge inside and stitch by hand using blind stitch.



Congratulations & enjoy



artgalleryfabrics.com

NOTE: While all possible care has been taken to ensure the accuracy of this pattern, We are not responsible for printing errors or the way in which individual work varies.

Please read instructions carefully before starting the construction of this quilt. If desired, wash and iron your fabrics before starting to cut.

© 2021 Courtesy of Art Gallery Quilts LLC. All Rights Reserved.